



SAFETY DATA SHEET

COLOURSTONE BOUND RESIN PART B

Page: 1

Compilation date: 01/08/2011

Revision date: 10/03/2016

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: COLOURSTONE BOUND RESIN PART B

REACH registered number(s): EXEMPT UNDER REACH IN ACCORDANCE WITH ARTICLE II, SECTION 9

CAS number: 28182-81-2

EINECS number: 931-274-8

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Polyurethane Binder. Specifically for use with Colourbound Resin Part A

1.3. Details of the supplier of the safety data sheet

Company name: Colourstone
72 Fairmile Road
Christchurch
Dorset
BH23 2LL
United Kingdom

Tel: 01202 499270

Email: enquiries@colour-stone.co.uk

1.4. Emergency telephone number

Emergency tel: 0777 3040391
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Acute Tox. 4: H332; Skin Sens. 1: H317; STOT SE 3: H335; -: EUH208

Most important adverse effects: Contains hexamethylene-di-isocyanate. May produce an allergic reaction. Harmful if inhaled. May cause an allergic skin reaction. May cause respiratory irritation.

2.2. Label elements

Label elements under CLP:

Hazard statements: EUH208: Contains hexamethylene-di-isocyanate. May produce an allergic reaction.
H332: Harmful if inhaled.
H317: May cause an allergic skin reaction.
H335: May cause respiratory irritation.

Hazard pictograms: GHS07: Exclamation mark



[cont...]

SAFETY DATA SHEET
COLOURSTONE BOUND RESIN PART B

Page: 2

Signal words: Warning

Precautionary statements: P260: Do not breathe dust/fumes/gas/mist/vapours/spray.
P285: In case of inadequate ventilation wear respiratory protection.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P333+313: If skin irritation or rash occurs: Get medical advice/attention.
P302+352: IF ON SKIN: Wash with plenty of soap and water.
P403+233: Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ALIPHATIC POLYISOCYANATE OLIGOMER - REACH registered number(s): 01-2119485796-17-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
500-060-2	28182-81-2	-	Acute Tox. 3: H331; Skin Sens. 1: H317; STOT SE 3: H335	>90%

HEXAMETHYLENE-DI-ISOCYANATE - REACH registered number(s): 01-2119457571-37

212-485-8	822-06-0	-	Acute Tox. 3: H331; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317	<1%
-----------	----------	---	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.
Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion: Wash out mouth with water. Consult a doctor.
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.
Eye contact: There may be irritation and redness. The eyes may water profusely.
Ingestion: There may be soreness and redness of the mouth and throat.
Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

[cont...]

SAFETY DATA SHEET
COLOURSTONE BOUND RESIN PART B

Page: 3

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

[cont...]

SAFETY DATA SHEET
COLOURSTONE BOUND RESIN PART B

Page: 4

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

HEXAMETHYLENE-DI-ISOCYANATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.02 mg/m ³	0.07 mg/m ³	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Barely perceptible odour

Evaporation rate: Negligible

Oxidising: No data available.

Solubility in water: Insoluble, reacts with water

Also soluble in: Most organic solvents.

Viscosity: Viscous

Kinematic viscosity: 1400

Viscosity test method: cps @ 25C

Boiling point/range°C: >35

Melting point/range°C: No data available.

Flammability limits %: lower: No data available.

upper: No data available.

Flash point°C: 252

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available.

Vapour pressure: No data available.

Relative density: 1.16

pH: Approx. 7

VOC g/l: No data available.

9.2. Other information

Other information: No data available.

[cont...]

SAFETY DATA SHEET
COLOURSTONE BOUND RESIN PART B

Page: 5

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HEXAMETHYLENE-DI-ISOCYANATE

IVN	MUS	LD50	5600	µg/kg
ORL	MUS	LD50	350	mg/kg
ORL	RAT	LD50	710	µl/kg

Relevant hazards for substance:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

[cont...]

SAFETY DATA SHEET
COLOURSTONE BOUND RESIN PART B

Page: 6

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Either return any unused product to the supplier, or Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Allow container residue to moisture cure to an inert polyurethane resin. Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.
H315: Causes skin irritation.

[cont...]

SAFETY DATA SHEET
COLOURSTONE BOUND RESIN PART B

Page: 7

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.